



Digital caliper with data output, Measuring range: 200 mm



Order data

Order number	412729 200
GTIN	4059192002169
Item class	43A

Description

Version:

Easy-to-read, high-contrast LCD display with 8.5 mm high characters. Modern energy-efficient measurement system, operational life approx. 3 years. The reference-lock function prevents measurement errors arising from accidentally touching the control buttons. Lapped slides, the measuring faces are precision lapped.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498940.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

Measured value saving: MAHR reference-lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 50 mm

Technical description

Reversible reading	mm / inch
Depth gauge available	yes
Depth gauge	flat

Standard	DIN 862
Calibration	A1
Jaw length	50 mm
Working time	approx. 3 years
Digit height LCD display	8.5 mm
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 200 mm
Measured value saving	MAHR reference-lock system
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200

Calibration Calipers / depth gauges maximum measuring range 200 mm

021000 200

Accessories

Receiver / USB keyboard interface Type

498965

Transmitter Type S4E

498966 S4E

Button cell / special battery Battery type CR2032

081560 CR2032

Connecting cable Type USB2

498940 USB2

Connecting cable Type D2

498940 D2

Connecting cable Type R2

498940 R2

Multi-receiver / USB keyboard interface Type

498975