



## Digital caliper IP67, Measuring range: 200 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 412733 200    |
| GTIN         | 4059192058289 |
| Item class   | 43A           |

### Description

#### Version:

Clearly legible, high-contrast LCD display. Waterproof inductive measurement system with reference-lock function. The measuring faces are precision lapped.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1 battery No. 081560 size CR2032

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: MAHR Reference Lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 50 mm

### Technical description

|                 |             |
|-----------------|-------------|
| Jaw length      | 50 mm       |
| Scale divisions | 0.01 mm     |
| Scale divisions | 0.0005 inch |

|   |                            |
|---|----------------------------|
| Measured value saving                                   | MAHR Reference Lock system |
| Measuring range   | 0 - 200 mm                 |
| Standard  | DIN 862                    |
| Depth gauge available                                   | yes                        |
| Calibration   | A1                         |
| Reversible reading                                      | mm / inch                  |
| Error limit   | 0.03 mm                    |
| Depth gauge   | flat                       |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032              |
| Number of batteries contained                           | 1                          |
| IP Index of Protection                                  | IP 67                      |
| Power supply  | Battery-powered            |
| Measurement technology                                  | digital                    |
| Material  | Stainless steel, INOX      |
| all parts   | hardened                   |
| Packaging   | sturdy box                 |
| Type of product   | Vernier caliper standard   |

## Services

|  |            |
|--|------------|
| Calibration Calipers / depth gauges maximum measuring range 200 mm       | 011030 200 |
| Labelling laser-etched Type  | 018940     |
| DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm | 011050 200 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm | 021010 200 |
| Calibration Calipers / depth gauges maximum measuring range 200 mm       | 021000 200 |

## Accessories

Button cell / special battery Battery type CR2032

081560 CR2032