



## Digital caliper IP67, Measuring range: 300 mm



### Order data

Order number	412733 300
GTIN	4059192058302
Item class	43A

### Description

#### Version:

Clearly legible, high-contrast LCD display. Waterproof inductive measurement system with reference-lock function. The measuring faces are precision lapped. Without depth gauge.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Standard:

To manufacturer's standard

#### Supplied with:

1 battery No. 081560 size CR2032

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

IP Index of Protection: IP 67

Measured value saving: MAHR Reference Lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 64 mm

### Technical description

Standard	DIN 862
Scale divisions	0.0005 inch

Scale divisions	0.01 mm
Jaw length	64 mm
Calibration	A1
Error limit	0.04 mm
Measured value saving	MAHR Reference Lock system
Reversible reading	mm / inch
Measuring range	0 - 300 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300
Calibration Calipers / depth gauges maximum measuring range 300 mm	021000 300
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	021010 300

## Accessories

Plastic case Type MS300	412470 MS300
-------------------------	--------------

Plastic case Type MS300	412468 MS300
Button cell / special battery Battery type CR2032	081560 CR2032