



Digital caliper IP67 i-wi, Measuring range: 150 mm



Order data

Order number	412738 150
GTIN	4059192002480
Item class	43A

Description

Version:

Very large LCD display with 11 mm character height. Integral i-wi wireless data interface. Resistant to dust and moisture. Service life approx. 3 years.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

i-wi radio receiver No. 498912.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: MAHR reference-lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Working time	approx. 3 years
--------------	-----------------

Depth gauge	flat
Depth gauge available	yes
Reversible reading	mm / inch
Digit height LCD display	11 mm
Calibration	A1
Jaw length	40 mm
Standard	DIN 862
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	MAHR reference-lock system
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	MAHR i-wi radio system
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
	021010 200

DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm

Calibration Calipers / depth gauges maximum measuring range 200 mm

021000 200

Accessories

Plastic case Type MS150

412470 MS150

Radio receivers for Mahr i-wi Type STICK

498912 STICK

Plastic case Type MS150

412468 MS150

Button cell / special battery Battery type CR2032

081560 CR2032