

Mahr**Digital caliper IP67 with rod type depth gauge, data output and ceramic measuring faces, Measuring range: 150 mm****Order data**

Order number	412743 150
GTIN	4059192002282
Item class	43A

Description**Version:**

Clearly legible, high-contrast LCD display. Waterproof inductive measurement system with reference-lock function. The measuring faces are precision lapped.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498940.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: Ø 1.5

IP Index of Protection: IP 67

Measured value saving: MAHR reference-lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Jaw length	40 mm
Guidance	Raised slides
Calibration	A1
Depth gauge available	yes
Depth gauge	Ø 1.5
Auto switch-off	yes
Reversible reading	mm / inch
Standard	DIN 862
Working time	approx. 3 years
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	MAHR reference-lock system
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm

011030 200

Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

Accessories

Connecting cable Type USB2	498940 USB2
Plastic case Type MS150	412468 MS150
Plastic case Type MS150	412470 MS150
Button cell / special battery Battery type CR2032	081560 CR2032
Battery compartment cover	412235
Connecting cable Type D2	498940 D2
Connecting cable Type R2	498940 R2