HOLEX

Digital caliper IP67, Measuring range: 150 mm



Order data

Order number	412751 150
GTIN	4045197347411
Item class	42A

Description

Version:

Large high-contrast digital display. The measuring faces are precision-lapped. The caliper is resistant to water and dust. After 2 hours without movement, the control system shuts down the caliper automatically. Shock-resistant plastic casing.

Standard:

Clearly legible, high-contrast digital display. The calliper is resistant to water, coolant, oil, and dust. The measuring faces are precision lapped.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Battery No. 081560 size CR2032. Packaging: sturdy box Standard: DIN 862 Reversible reading: mm / inch Depth gauge: flat IP Index of Protection: IP 67 Calibration: A1 Scale divisions: 0.01 mm Scale divisions: 0.0005 inch Error limit: 0.03 mm Jaw length: 40 mm

Technical description

Material of the housing

Plastic

Depth gauge available	yes
Calibration	A1
Reversible reading	mm / inch
Jaw length	40 mm
Depth gauge	flat
Auto switch-off	yes
Standard	DIN 862
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200

Accessories

Plastic case Type MS150	412468 MS150

© Hoffmann GmbH Qualitätswerkzeuge

Plastic case Type MS150	412470 MS150
Button cell / special battery Battery type CR2032	081560 CR2032
Depth gauge holder	412230