

# Digital caliper with outwards-facing measuring jaws, Measuring range: 150 mm



## **Order data**

Order number	412755 150
GTIN	4059192002367
Item class	43A

## **Description**

#### **Version:**

Clearly legible, high-contrast LCD display. Waterproof inductive measurement system with reference-lock function.

#### **Function:**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

### **Supplied with:**

1 battery No. 081560 size CR2032

#### **Optional extras:**

Data cable No. 498940. Packaging: sturdy box

Standard: Manufacturer's standard Reversible reading: mm / inch IP Index of Protection: IP 67

Measured value saving: MAHR reference-lock system

Calibration: A1

Scale divisions: 0.01 mm Scale divisions: 0.0005 inch

Error limit: 0.03 mm Jaw length: 40 mm

# **Technical description**

Reversible reading mm / inch

Jaw length	40 mm
Standard	Manufacturer's standard
Type of caliper jaws	angled outwards
Calibration	A1
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	MAHR reference-lock system
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	USB interface
Interface	Digimatic interface
Interface	RS232 interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

# Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200

# **Accessories**

Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable with data key Type D2	498940 D2
Connecting cable with data key Type R2	498940 R2
Connecting cable with data key Type USB2	498940 USB2
Battery compartment cover	412235