

# Digital caliper TESA-CAL IP67 with rod type depth gauge, Measuring range: 150 mm



### **Order data**

Order number	412759 150
GTIN	7630041148640
Item class	45A

## **Description**

#### **Version:**

Large high-contrast display with 11 mm character height. More than 12000 hours service life, automatic standby after 10 minutes and automatic shutdown after 2 hours. ABS measuring mode. All-round protection against liquids.

### **Function:**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### **Application:**

External, internal, step and depth measurements.

#### **Supplied with:**

1 battery No. 081560 size CR2032.

Packaging: sturdy box

Standard: Manufacturer's standard Reversible reading: mm / inch

Depth gauge: Ø 1.5

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm Scale divisions: 0.0005 inch

Error limit: 0.03 mm Jaw length: 40 mm

# **Technical description**



Working time	12000 hours
Measured value saving	Once-off setting of the zero position
Error limit	0.03 mm
Calibration	A1
Scale divisions	0.01 mm
Auto switch-off	yes
Measurement value and zero point preserved after reactivation from standby	yes
Standard	Manufacturer's standard
Jaw length	40 mm
Measuring range	0 - 150 mm
Digit height LCD display	11 mm
Scale divisions	0.0005 inch
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Reversible reading	mm / inch
Automatic stand-by circuit.	yes
Depth gauge	Ø 1.5
Depth gauge available	yes
IP Index of Protection	IP 67
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Labelling laser-etched Type	018940
	011030 200



Calibration Calipers / depth gauges maximum measuring range 200 mm	
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Accessories	
Button cell / special battery Battery type CR2032	081560 CR2032