

Digital caliper TESA-CAL IP67, Measuring range: 150 mm



Order data

| Order number | 412760 150 |
|--------------|---------------|
| GTIN | 7630041148633 |
| Item class | 45A |

Description

Version:

Large high-contrast display with 11 mm character height. More than 12000 hours service life, automatic standby after 10 minutes and automatic shutdown after 2 hours. ABS measuring mode. All-round protection against liquids.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

External, internal, step and depth measurements.

Supplied with:

1 battery No. 081560 size CR2032.

Packaging: sturdy box

Standard: Manufacturer's standard Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm Scale divisions: 0.0005 inch

Error limit: 0.03 mm Jaw length: 40 mm

Technical description

Scale divisions 0.01 mm



| Measured value saving | Once-off setting of the zero position |
|--|---------------------------------------|
| Digit height LCD display | 11 mm |
| Scale divisions | 0.0005 inch |
| Error limit | 0.03 mm |
| Measuring range | 0 - 150 mm |
| Reversible reading | mm / inch |
| Working time | 12000 hours |
| Standard | Manufacturer's standard |
| Auto switch-off | yes |
| Depth gauge | flat |
| Number of batteries contained | 1 |
| Calibration | A1 |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032 |
| Measurement value and zero point preserved after reactivation from standby | yes |
| Jaw length | 40 mm |
| Automatic stand-by circuit. | yes |
| Depth gauge available | yes |
| IP Index of Protection | IP 67 |
| Power supply | Battery-powered |
| Measurement technology | digital |
| Material | Stainless steel, INOX |
| all parts | hardened |
| Packaging | sturdy box |
| Type of product | Vernier caliper standard |
| | |

Services

| Labelling laser-etched Type | 018940 |
|--|------------|
| Calibration Calipers / depth gauges maximum measuring range 200 mm | 011030 200 |

Data sheet

⚠ Hoffmann Group

| DAkkS calibration Calipers / depth gauges maximum | |
|---|--|
| measuring range 200 mm | |

011050 200

Accessories

Button cell / special battery Battery type CR2032

081560 CR2032