

### Digital caliper TESA-CAL IP67, Measuring range: 200 mm



### **Order data**

Order number	412760 200
GTIN	7630041148657
Item class	45A

### **Description**

#### Version:

Large high-contrast display with 11 mm character height. More than 12000 hours service life, automatic standby after 10 minutes and automatic shutdown after 2 hours. ABS measuring mode. All-round protection against liquids. With thumb roller.

#### **Function:**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### **Application:**

External, internal, step and depth measurements.

#### **Supplied with:**

1 battery No. 081560 size CR2032.

Packaging: sturdy box

Standard: Manufacturer's standard Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm Scale divisions: 0.0005 inch

Error limit: 0.03 mm Jaw length: 50 mm

## **Technical description**

Error limit	0.03 mm
-------------	---------



Measured value saving	Once-off setting of the zero position
Reversible reading	mm / inch
Calibration	A1
Measuring range	0 - 200 mm
Drive roller	yes
Number of batteries contained	1
Scale divisions	0.01 mm
Jaw length	50 mm
Auto switch-off	yes
Automatic stand-by circuit.	yes
Standard	Manufacturer's standard
Depth gauge available	yes
Depth gauge	flat
Article no of the battery / rechargeable battery fitted	081560 CR2032
Working time	12000 hours
Scale divisions	0.0005 inch
Measurement value and zero point preserved after reactivation from standby	yes
Digit height LCD display	11 mm
IP Index of Protection	IP 67
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

# Services

Labelling laser-etched Type	018940
	011030 200



Calibration Calipers / depth gauges maximum measuring range 200 mm	
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Accessories	
Button cell / special battery Battery type CR2032	081560 CR2032