



TESA TWIN-CAL digital caliper with rod type depth gauge, Measuring range: 150 mm



Order data

Order number	412765 150
GTIN	7630041106145
Item class	45A

Description

Version:

Large high-contrast display with 11 mm character height. More than 12,000 operating hours, automatic standby after 10 min and automatic shutdown after 2 h. ABS measurement mode, integral TLC port for data transmission.

With thumb roller.

Application:

External, internal, step and depth measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Supplied with:

1 battery No. 081560 CR2032.

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Standard: Manufacturer's standard

Reversible reading: mm / inch

Depth gauge: flat

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Jaw length	40 mm
Calibration	A1
Depth gauge available	yes
Depth gauge	flat
Drive roller	yes
Auto switch-off	yes
Automatic stand-by circuit.	yes
Reversible reading	mm / inch
Standard	Manufacturer's standard
Working time	12000 h
Digit height LCD display	11 mm
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	Once-off setting of the zero position
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Interface	USB interface
Interface	TESA Link Connector TLC
Interface	Digimatic interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

Accessories

Radio receiver TWIN Station Type STATION	498917 STATION
Plastic case Type MS150	412470 MS150
Receiver / USB keyboard interface Type	498965
Stat-Express software	498926
Software Data-Direct	498925
Multi-receiver / USB keyboard interface Type	498975
Button cell / special battery Battery type CR2032	081560 CR2032
Data cable TLC, 2 m Type D	498918 D
Data cable TLC, 2 m Type USB	498918 USB
Plastic case Type MS150	412468 MS150
Transmitter Type S121	498966 S121
Radio transmitter TLC-TWIN Type SENDER	498916 SENDER