




## TESA TWIN-CAL digital caliper, Measuring range: 150 mm



### Order data

Order number	412766 150
GTIN	7630041106176
Item class	45A

### Description

#### Version:

Large high-contrast display with 11 mm character height. More than 12,000 operating hours, automatic standby after 10 min and automatic shutdown after 2 h. ABS measurement mode, integral TLC port for data transmission. Without thumb roller.

#### Application:

External, internal, step and depth measurements.

#### Supplied with:

1 battery No. 081560 CR2032.

#### Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Standard: Manufacturer's standard

Reversible reading: mm / inch

Depth gauge: flat

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

### Technical description

Reversible reading	mm / inch
Auto switch-off	yes

Working time	12000 h
Depth gauge available	yes
Jaw length	40 mm
Standard	Manufacturer's standard
Calibration	A1
Digit height LCD display	11 mm
Depth gauge	flat
Automatic stand-by circuit.	yes
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	Once-off setting of the zero position
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Interface	TESA Link Connector TLC
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
	011050 200

DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

## Accessories

Software Data-Direct	498925
Stat-Express software	498926
Radio receiver TWIN Station Type STATION	498917 STATION
Data cable TLC, 2 m Type USB	498918 USB
Transmitter Type S121	498966 S121
Radio transmitter TLC-TWIN Type SENDER	498916 SENDER
Plastic case Type MS150	412470 MS150
Receiver / USB keyboard interface Type	498965
Button cell / special battery Battery type CR2032	081560 CR2032
Plastic case Type MS150	412468 MS150
Data cable TLC, 2 m Type D	498918 D
Multi-receiver / USB keyboard interface Type	498975