



Digital external groove caliper with rod type depth gauge, Measuring range: 150 mm



Order data

Order number	412772 150
GTIN	4059192057183
Item class	43A

Description

Version:

Very large LCD display with 11 mm character height. Integral i-wi wireless data interface. Resistant to dust and moisture. Service life approx. 3 years.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

i-wi radio receiver No. 498912.

IP Index of Protection: IP 67

Depth gauge: Ø 1.5

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Scale divisions	0.0005 inch
Error limit	0.03 mm
Scale divisions	0.01 mm
Jaw length	40 mm

Depth gauge	Ø 1.5
Measuring range	150 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
all parts	hardened
Material	Stainless steel, INOX
Reversible reading	mm / inch
Measured value saving	MAHR reference-lock system
Interface	MAHR i-wi radio system
Packaging	sturdy box
Calibration	A1
Measurement technology	digital
Type of product	Caliper, special type

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200

Accessories

Radio receivers for Mahr i-wi Type STICK	498912 STICK
Plastic case Type MS150	412470 MS150
Button cell / special battery Battery type CR2032	081560 CR2032
Plastic case Type MS150	412468 MS150