



Digital caliper TWIN-CAL IP67, Measuring range: 200 mm



Order data

Order number	412786 200
GTIN	7630041106312
Item class	45A

Description

Version:

Large high-contrast display with 11 mm character height. More than 12,000 hours service life, automatic standby after 10 minutes and automatic shutdown after 2 hours. ABS measurement mode, integral TLC port for data transmission. All-round protection against liquids. Casing with steel protection plate and "Soft Touch" surface. With thumb roller.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

External, internal, step and depth measurements.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Standard: Manufacturer's standard

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 50 mm

Technical description

Automatic stand-by circuit.	yes
Standard	Manufacturer's standard
Working time	12000 h
Digit height LCD display	11 mm
Depth gauge available	yes
Reversible reading	mm / inch
Calibration	A1
Auto switch-off	yes
Drive roller	yes
Depth gauge	flat
Jaw length	50 mm
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 200 mm
Measured value saving	once-off setting of the zero position
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	Digimatic interface
Interface	USB interface
Interface	TESA Link Connector TLC
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

Accessories

Radio transmitter TLC-TWIN Type SENDER	498916 SENDER
Stat-Express software	498926
Button cell / special battery Battery type CR2032	081560 CR2032
Radio receiver TWIN Station Type STATION	498917 STATION
Data cable TLC, 2 m Type D	498918 D
Software Data-Direct	498925
Data cable TLC, 2 m Type USB	498918 USB