



## Digital caliper TWIN-CAL IP67, Measuring range: 300 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 412786 300    |
| GTIN         | 7630041106329 |
| Item class   | 45A           |

### Description

#### Version:

Large high-contrast display with 11 mm character height. More than 12,000 hours service life, automatic standby after 10 minutes and automatic shutdown after 2 hours. ABS measurement mode, integral TLC port for data transmission. All-round protection against liquids. Casing with steel protection plate and "Soft Touch" surface. With thumb roller.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Application:

External, internal, step and depth measurements.

#### Supplied with:

1 battery No. 081560 size CR2032

#### Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Standard: Manufacturer's standard

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 64 mm

### Technical description

|   |                                       |
|---|---------------------------------------|
| Auto switch-off   | yes                                   |
| Jaw length  | 64 mm                                 |
| Working time  | 12000 h                               |
| Digit height LCD display                                | 11 mm                                 |
| Drive roller  | yes                                   |
| Depth gauge   | flat                                  |
| Calibration   | A1                                    |
| Automatic stand-by circuit.                             | yes                                   |
| Depth gauge available                                   | yes                                   |
| Reversible reading                                      | mm / inch                             |
| Standard  | Manufacturer's standard               |
| Scale divisions   | 0.01 mm                               |
| Scale divisions   | 0.0005 inch                           |
| Error limit   | 0.03 mm                               |
| Measuring range   | 0 - 300 mm                            |
| Measured value saving                                   | once-off setting of the zero position |
| Number of batteries contained                           | 1                                     |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032                         |
| IP Index of Protection                                  | IP 67                                 |
| Power supply  | Battery-powered                       |
| Interface   | Digimatic interface                   |
| Interface   | USB interface                         |
| Interface   | TESA Link Connector TLC               |
| Measurement technology                                  | digital                               |
| Material  | Stainless steel, INOX                 |
| all parts   | hardened                              |
| Packaging   | sturdy box                            |
| Type of product   | Vernier caliper standard              |

## Services

|  |            |
|--|------------|
| Calibration Calipers / depth gauges maximum measuring range 300 mm       | 011030 300 |
| Labelling laser-etched Type  | 018940     |
| DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm | 011050 300 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm | 021010 300 |
| Calibration Calipers / depth gauges maximum measuring range 300 mm       | 021000 300 |

## Accessories

|   |                |
|---|----------------|
| Radio receiver TWIN Station Type STATION          | 498917 STATION |
| Radio transmitter TLC-TWIN Type SENDER            | 498916 SENDER  |
| Software Data-Direct                              | 498925         |
| Plastic case Type MS300                           | 412470 MS300   |
| Data cable TLC, 2 m Type D                        | 498918 D       |
| Button cell / special battery Battery type CR2032 | 081560 CR2032  |
| Plastic case Type MS300                           | 412468 MS300   |
| Data cable TLC, 2 m Type USB                      | 498918 USB     |
| Stat-Express software                             | 498926         |