

HOLEX®
Digital caliper ABS + accessories set, Measuring range: 150 mm

Order data

Order number	412815 150
GTIN	4062406156497
Item class	42A

Description
Version:

Set consisting of a digital caliper and accessories set.

- **Digital caliper with absolute scale, no zeroing required. Large high-contrast digital display. The measuring faces are precision-lapped. With sturdy metal casing.**
- **Accessories set for digital caliper – permits measurement of recesses, slots and pitches between holes.**

Supplied with:

1× digital caliper No. 412821 size 150.

1 battery No. 081560 size CR2032.

1× accessory set No. 412747 size 3.5 **consisting of:**

2 pairs of contact point carriers short and long.

3 pairs of measuring tips with measuring discs Ø 6 mm, Ø 10 mm, Ø 12.5 mm.

2 pairs of measuring tips with anvil cones Ø 9 mm, 60° and Ø 12 mm, 60°.

1 pair of measuring tips with measuring cylinders Ø 1.5×9 mm.

1× spring system for constant gauging force.

1× hexagon key L-wrench.

1× depth extension base 75 mm.

Supplied in a sturdy plastic box.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

Measured value saving: once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Number of batteries contained	1
Error limit	0.03 mm
Measured value saving	once-off setting of the zero position
Scale divisions	0.0005 inch
Jaw length	40 mm
Calibration	A1
Standard	DIN 862
Scale divisions	0.01 mm
Measuring range	0 - 150 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Measurement face	precision lapped
Depth gauge available	yes
Reversible reading	mm / inch
Depth gauge	flat
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Labelling laser-etched Type	018940

Accessories

Button cell / special battery International size CR2032	081560 CR2032
Depth gauge base	412710
Accessories set for digital calipers maximum jaw thickness 3,5 mm	412747 3,5