



## Digital caliper ABS, Measuring range: 200 mm



### Order data

Order number	412821 200
GTIN	4045197770257
Item class	42A

### Description

#### Version:

Large high-contrast digital display. The measuring faces are precision-lapped. Digital caliper with **absolute scale**, no zeroing required. Electronics switch off automatically after approx. 5 minutes and switch on again as soon as the tool is moved.

- **Very high accuracy due to the glass scale.**
- **The electronics are decoupled from the casing and incorporated directly in the sliding part. The gauging force is transmitted directly to the measurement jaws. This reduces the liability of the caliper to errors and increases the working life.**
- **With sturdy metal body.**

#### Supplied with:

Supplied with battery No. 081560 size CR2032.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 50 mm

### Technical description

Measuring range	0 - 200 mm
-----------------	------------

Auto switch-off	yes
Jaw length	50 mm
Depth gauge	flat
Scale divisions	0.0005 inch
Material of the housing	Metal
Standard	DIN 862
Scale divisions	0.01 mm
Error limit	0.03 mm
Reversible reading	mm / inch
Depth gauge available	yes
Calibration	A1
Measured value saving	Once-off setting of the zero position
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200
	021010 200

DAkKS calibration Calipers / depth gauges maximum  
measuring range 200 mm

### Accessories

Button cell / special battery Battery type CR2032

081560 CR2032

Screw for depth gauge holder

412230