



Digital caliper IP54 with data output including a set of accessories, Measuring range: 150 mm



Order data

Order number	412840 150
GTIN	4062406127367
Item class	41A

Description

Version:

Digital caliper with comprehensive accessories - **permits measurement of recesses, slots and hole pitches.**

- **Easy-to-read, high-contrast LCD display with 11.5 mm character height.**
- **Very long battery running time due to modern energy-efficient measurement system.**
- **Ergonomic housing with easy-grip Santoprene® components.**

Function:

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Supplied with:

- 1× **IP54** digital caliper with data output No. 412680 size 150.
 - 1 battery No. 081560 size CR2032.
 - 2 pairs of contact point carriers short and long.
 - 3 pairs of measuring tips with measuring discs Ø 6 mm, Ø 10 mm, Ø 12.5 mm.
 - 2 pairs of measuring tips with anvil cones Ø 9 mm, 60° and Ø 12 mm, 60°.
 - 1 pair of measuring tips with measuring cylinders Ø 1.5×9 mm.
 - 1× spring system for constant gauging force.
 - 1× hexagon key L-wrench.
 - 1× depth extension base 75 mm.
- Supplied in a sturdy plastic box.

Spare part:

Data output cap No. 412237 size D, battery holder No. 412237 size B.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 54

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Scale divisions	0.0005 inch
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Reversible reading	mm / inch
Scale divisions	0.01 mm
Error limit	0.03 mm
Calibration	A1
Measuring range	0 - 150 mm
Jaw length	40 mm
Depth gauge	flat
Standard	DIN 862
Digit height LCD display	11.5 mm
Depth gauge available	yes
IP Index of Protection	IP 54
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened

Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Labelling laser-etched Type	018940

Accessories

Button cell / special battery International size CR2032	081560 CR2032
---	---------------