#### **Å**Garant<sup>\*</sup>

Digital caliper IP67 with data output including a set of accessories, Measuring range: 150 mm



## Order data

Order number	412845 150
GTIN	4062406127374
Item class	41A

### Description

#### Version:

Digital caliper with comprehensive accessories - **permits measurement of recesses, slots and hole pitches.** 

• Easy-to-read, high-contrast LCD display with 11.5 mm character height.

· Very long battery running time due to modern energy-efficient measurement system.

· Ergonomic housing with easy-grip Santoprene® components.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1× **IP67** digital caliper with data output No. 412690 size 150.

1 battery No. 081560 size CR2032.

2 pairs of contact point carriers short and long.

3 pairs of measuring tips with measuring discs  $\emptyset$  6 mm,  $\emptyset$  10 mm,  $\emptyset$  12.5 mm.

2 pairs of measuring tips with anvil cones  $\emptyset$  9 mm, 60° and  $\emptyset$  12 mm, 60°.

1 pair of measuring tips with measuring cylinders  $\emptyset$  1.5×9 mm.

1× spring system for constant gauging force.

1× hexagon key L-wrench.

 $1 \times$  depth extension base 75 mm.

Supplied in a sturdy plastic box.

#### Spare part:

Data output cap No. 412237 size D, battery holder No. 412237 size B. Packaging: sturdy box Standard: DIN 862 Reversible reading: mm / inch Depth gauge: flat IP Index of Protection: IP 67 Calibration: A1 Scale divisions: 0.01 mm Scale divisions: 0.0005 inch Error limit: 0.03 mm Jaw length: 40 mm

## **Technical description**

Article no of the battery / rechargeable battery fitted	081560 CR2032
Error limit	0.03 mm
Standard	DIN 862
Calibration	A1
Scale divisions	0.01 mm
Reversible reading	mm / inch
Depth gauge	flat
Scale divisions	0.0005 inch
Measuring range	0 - 150 mm
Jaw length	40 mm
Number of batteries contained	1
Depth gauge available	yes
Digit height LCD display	11.5 mm
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened

© Hoffmann GmbH Qualitätswerkzeuge

Packaging	sturdy box
Type of product	Vernier caliper standard
Services	
Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Labelling laser-etched Type	018940

# Accessories

Button cell / special battery International size CR2032 081560 CR2032