

**Digital caliper MarCal with measuring tips, Measuring range: 500 mm****Order data**

Order number	415320 500
GTIN	4059192002923
Item class	43A

Description**Version:**

Direct reading from large and clear digital display. Precision lapped measuring faces.

Perforated measurement jaws.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498940.

Reversible reading: mm / inch

IP Index of Protection: IP 65

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 150 mm

Internal jaw Ø: 20 mm

Technical description

Internal jaw Ø	20 mm
Jaw length	150 mm
Measuring range	0 - 500 mm

Calibration	A1
Reversible reading	mm / inch
Scale divisions	0.0005 inch
Scale divisions	0.01 mm
Error limit	0.04 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	Digimatic interface
Interface	RS232 interface
Measured value saving	MAHR reference-lock system
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

Services

Calibration Calipers / depth gauges maximum measuring range 500 mm	011030 500
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 500 mm	011050 500

Accessories

Connecting cable with data key Type D2	498940 D2
Connecting cable with data key Type USB2	498940 USB2

Connecting cable with data key Type R2	498940 R2
Button cell / special battery Battery type CR2032	081560 CR2032