



Digital caliper MarCal with measuring tips, Measuring range: 750 mm



Order data

Order number	415320 750
GTIN	4059192002947
Item class	43A

Description

Version:

Direct reading from large and clear digital display. Precision lapped measuring faces.

Perforated measurement jaws.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498940.

Reversible reading: mm / inch

IP Index of Protection: IP 65

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.05 mm

Jaw length: 150 mm

Internal jaw Ø: 20 mm

Technical description

Reversible reading	mm / inch
Jaw length	150 mm
Calibration	A1

Measuring range	0 - 750 mm
Internal jaw Ø	20 mm
Scale divisions	0.0005 inch
Scale divisions	0.01 mm
Error limit	0.05 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	Digimatic interface
Interface	RS232 interface
Measured value saving	MAHR reference-lock system
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

Services

Calibration Calipers / depth gauges maximum measuring range 1000 mm	011030 1000
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	011050 1000

Accessories

Connecting cable with data key Type USB2	498940 USB2
Connecting cable with data key Type R2	498940 R2

Connecting cable with data key Type D2	498940 D2
Button cell / special battery Battery type CR2032	081560 CR2032