



## Digital caliper MarCal without measuring tips, Measuring range: 300 mm



### Order data

Order number	415322 300
GTIN	4059192002916
Item class	43A

### Description

#### Version:

**Direct reading from large and clear digital display. Precision lapped measuring faces.**

#### Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1 battery No. 081560 size CR2032

#### Optional extras:

Data cable No. 498940.

Reversible reading: mm / inch

IP Index of Protection: IP 65

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 90 mm

Internal jaw  $\varnothing$ : 10 mm

### Technical description

Measuring range	0 - 300 mm
Jaw length	90 mm
Calibration	A1
Internal jaw $\varnothing$	10 mm

Reversible reading	mm / inch
Scale divisions	0.0005 inch
Scale divisions	0.01 mm
Error limit	0.03 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	Digimatic interface
Interface	RS232 interface
Measured value saving	MAHR reference-lock system
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

## Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300

## Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable with data key Type D2	498940 D2
Connecting cable with data key Type USB2	498940 USB2

Connecting cable with data key Type R2

498940 R2