



## Digital caliper MarCal without measuring tips, Measuring range: 500 mm



### Order data

Order number	415322 500
GTIN	4059192002930
Item class	43A

### Description

#### Version:

**Direct reading from large and clear digital display. Precision lapped measuring faces.**

Perforated measurement jaws.

#### Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1 battery No. 081560 size CR2032

#### Optional extras:

Data cable No. 498940.

Reversible reading: mm / inch

IP Index of Protection: IP 65

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 150 mm

Internal jaw  $\varnothing$ : 20 mm

### Technical description

Measuring range	0 - 500 mm
Jaw length	150 mm
Reversible reading	mm / inch

Internal jaw Ø	20 mm
Calibration	A1
Scale divisions	0.0005 inch
Scale divisions	0.01 mm
Error limit	0.04 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	Digimatic interface
Interface	RS232 interface
Measured value saving	MAHR reference-lock system
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

## Services

Calibration Calipers / depth gauges maximum measuring range 500 mm	011030 500
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 500 mm	011050 500

## Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable with data key Type D2	498940 D2

Connecting cable with data key Type R2	498940 R2
Connecting cable with data key Type USB2	498940 USB2