



TWIN CAL digital workshop caliper IP67 with measuring tips, Measuring range: 1000 mm



Order data

Order number	415357 1000
GTIN	7630041106473
Item class	45A

Description

Version:

Large digital display 11 mm, "Soft touch" casing, automatic shut-down (2 h), TLC-TWIN interface for data transmission.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Reversible reading: mm / inch

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.05 mm

Jaw length: 150 mm

Internal jaw \varnothing : 20 mm

Technical description

Internal jaw \varnothing	20 mm
Jaw length	150 mm

Measuring range	0 - 1000 mm
Calibration	A1
Reversible reading	mm / inch
Scale divisions	0.0005 inch
Scale divisions	0.01 mm
Error limit	0.05 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	Digimatic interface
Interface	USB interface
Interface	TESA Link Connector TLC
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

Services

Calibration Calipers / depth gauges maximum measuring range 1000 mm	011030 1000
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	011050 1000

Accessories

Radio receiver TWIN Station Type STATION	498917 STATION
Data cable TLC, 2 m Type D	498918 D

Button cell / special battery Battery type CR2032	081560 CR2032
Radio transmitter TLC-TWIN Type SENDER	498916 SENDER
Data cable TLC, 2 m Type USB	498918 USB