



TWIN CAL digital workshop caliper IP67 with measuring tips, Measuring range: 300 mm



Order data

| | |
|--------------|---------------|
| Order number | 415357 300 |
| GTIN | 7630041106435 |
| Item class | 45A |

Description

Version:

Large digital display 11 mm, "Soft touch" casing, automatic shut-down (2 h), TLC-TWIN interface for data transmission.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Reversible reading: mm / inch

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 80 mm

Internal jaw \varnothing : 10 mm

Technical description

| | |
|-----------------|------------|
| Measuring range | 0 - 300 mm |
| Jaw length | 80 mm |

| | |
|---|-------------------------|
| Reversible reading | mm / inch |
| Calibration | A1 |
| Internal jaw Ø | 10 mm |
| Scale divisions | 0.0005 inch |
| Scale divisions | 0.01 mm |
| Error limit | 0.04 mm |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032 |
| Number of batteries contained | 1 |
| IP Index of Protection | IP 67 |
| Power supply | Battery-powered |
| Standard | Manufacturer's standard |
| Interface | Digimatic interface |
| Interface | USB interface |
| Interface | TESA Link Connector TLC |
| Measurement technology | digital |
| Material | Stainless steel, INOX |
| all parts | hardened |
| Packaging | sturdy box |
| Type of product | Workshop calipers |

Services

| | |
|--|------------|
| Calibration Calipers / depth gauges maximum measuring range 300 mm | 011030 300 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm | 011050 300 |

Accessories

| | |
|--|----------------|
| Radio receiver TWIN Station Type STATION | 498917 STATION |
| Data cable TLC, 2 m Type USB | 498918 USB |

| | |
|---|---------------|
| Radio transmitter TLC-TWIN Type SENDER | 498916 SENDER |
| Button cell / special battery Battery type CR2032 | 081560 CR2032 |
| Data cable TLC, 2 m Type D | 498918 D |