



## Digital workshop caliper IP67 with measuring tips, Measuring range: 800 mm



### Order data

Order number	415365 800
GTIN	2050001949653
Item class	46P

### Description

#### Version:

Very large high-contrast LCD display. Digit height 8 mm or 14 mm (from size 500 mm). With preset (dimension selection in advance). The caliper is resistant to water, emulsion, oil, and dust.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

Incl. battery No. 081560 size CR2032.

#### Optional extras:

Data cable No. 498948 size USB2.

Packaging: sturdy box

Reversible reading: mm / inch

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 150 mm

Internal jaw  $\varnothing$ : 10 mm

### Technical description

Error limit	0.04 mm
Jaw length	150 mm

Scale divisions	0.0005 inch
Reversible reading	mm / inch
Calibration	A1
Internal jaw Ø	10 mm
Scale divisions	0.01 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Workshop calipers

## Services

Calibration Calipers / depth gauges maximum measuring range 1000 mm	011030 1000
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	011050 1000
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	021010 1000
Calibration Calipers / depth gauges maximum measuring range 1000 mm	021000 1000

## Accessories

Connecting cable Type USB2	498948 USB2
----------------------------	-------------

Button cell / special battery Battery type CR2032

081560 CR2032