



Digital workshop caliper IP67 without measuring tips, Measuring range: 600 mm



Order data

| | |
|--------------|---------------|
| Order number | 415366 600 |
| GTIN | 2050001911889 |
| Item class | 46P |

Description

Version:

Very large high-contrast LCD display. Digit height 8 mm or 14 mm (from size 500 mm). With preset (dimension selection in advance). The caliper is resistant to water, emulsion, oil, and dust.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Incl. battery No. 081560 size CR2032.

Optional extras:

Data cable No. 498948 size USB2.

Packaging: sturdy box

Reversible reading: mm / inch

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.04 mm

Jaw length: 150 mm

Internal jaw \varnothing : 10 mm

Technical description

| | |
|----------------------------|-------|
| Internal jaw \varnothing | 10 mm |
| Calibration | A1 |

| | |
|---|-------------------------|
| Jaw length | 150 mm |
| Error limit | 0.04 mm |
| Reversible reading | mm / inch |
| Scale divisions | 0.01 mm |
| Scale divisions | 0.0005 inch |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032 |
| Number of batteries contained | 1 |
| IP Index of Protection | IP 67 |
| Power supply | Battery-powered |
| Standard | Manufacturer's standard |
| Interface | USB interface |
| Measurement technology | digital |
| Material | Stainless steel, INOX |
| all parts | hardened |
| Packaging | sturdy box |
| Type of product | Workshop calipers |

Services

| | |
|---|-------------|
| Calibration Calipers / depth gauges maximum measuring range 1000 mm | 011030 1000 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm | 011050 1000 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm | 021010 1000 |
| Calibration Calipers / depth gauges maximum measuring range 1000 mm | 021000 1000 |

Accessories

| | |
|----------------------------|-------------|
| Connecting cable Type USB2 | 498948 USB2 |
|----------------------------|-------------|

Button cell / special battery Battery type CR2032

081560 CR2032