

Mitutoyo
Carbon digital caliper, Measuring range: 1000 mm

Order data

Order number	415400 1000
GTIN	4946368125275
Item class	44A

Description
Version:

Measured result is displayed in easy-to-read digits.

With drive slide for constant measuring force. Extremely light. Selectable set-point (preset), selection of internal / external measurements (offset).

Function:

IP66: Protected against strong jets of water, and against temporary flooding and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size 357.

Optional extras:

Data cable No. 497085.

Packaging: sturdy box

IP Index of Protection: IP 66

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.06 mm

Jaw length: 150 mm

Internal jaw Ø: 20 mm

Weight: 1.25 kg

Technical description

Calibration	A1
Weight	1.25 kg
Jaw length	150 mm

Internal jaw Ø	20 mm
Measuring range	0 - 1000 mm
Scale divisions	0.01 mm
Error limit	0.06 mm
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
Battery type	SR44
IP Index of Protection	IP 66
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	Digimatic interface
Measured value saving	once-off setting of the zero position
Measurement technology	digital
Packaging	sturdy box
Type of product	Workshop calipers

Services

Calibration Calipers / depth gauges maximum measuring range 1000 mm	011030 1000
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	011050 1000

Accessories

Connecting cable with data switch Type D2	497085 D2
Connecting cable with data switch Type USB2	497085 USB2
Connecting cable with data switch Type D1	497085 D1
Receiver / USB keyboard interface Type	498965
Button cell / special battery Battery type 357	081560 357

Transmitter Type S11E	498966 S11E
Multi-receiver / USB keyboard interface Type	498975