



Digital universal caliper, Measuring range: 650 mm



Order data

Order number	417700 650
GTIN	2050001670847
Item class	46P

Description

Version:

Digital universal caliper for a variety of internal and external measurements, with exchangeable measuring tips. RS232C data output.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital caliper including 1 battery No. 081560 size CR2032. Interchangeable measuring tips with ball \varnothing 3 mm and clamping sleeve with M2.5 internal thread.

Optional extras:

For size 400 - 650 all replacement and special contact points No. 434900 - 4910 with M2.5 thread can be used, data cable No. 498948.

Note:

Other measuring tips on request.

IP Index of Protection: IP 67

Calibration: A1

Measuring range outside: 0 - 570 mm

Measuring range inside: 42 - 650 mm

Scale divisions: 0.01 mm

Error limit: 0.04 mm

Jaw length: 103 mm

Ball \varnothing measuring tips: 3 mm

Technical description

Calibration	A1
-------------	----

Measuring range outside	0 - 570 mm
IP Index of Protection	IP 67
Ball Ø measuring tips	3 mm
Measuring range	0 - 650 mm
Jaw length	103 mm
Measuring range inside	42 - 650 mm
Scale divisions	0.01 mm
Error limit	0.04 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232 interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Universal caliper

Services

Calibration Calipers / depth gauges maximum measuring range 1000 mm	011030 1000
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 1000 mm	011050 1000

Accessories

Carbide contact point Type 18/3	434910 18/3
---------------------------------	-------------

Connecting cable Type USB2	498948 USB2
Connecting cable Type R2	498948 R2
Button cell / special battery Battery type CR2032	081560 CR2032
Steel contact point Type 18/3	434900 18/3
Steel contact point Type 11/20	434900 11/20
Steel contact point Type 14	434900 14
Steel contact point Type 11/35	434900 11/35
Steel contact point Type 15	434900 15
Steel contact point Type 11	434900 11
Steel contact point Type 14/15	434900 14/15
Steel contact point Type 11/30	434900 11/30
Steel contact point Type 16	434900 16
Steel contact point Type 11/15	434900 11/15
Steel contact point Type 20	434900 20
Steel contact point Type 11/25	434900 11/25
Steel contact point Type 10	434900 10
Steel contact point Type 18/6	434900 18/6
Steel contact point Type 13	434900 13
Steel contact point Type 14/20	434900 14/20
Steel contact point Type 28	434900 28
Connection cable Duplex Type USB2	498950 USB2
Steel contact point Type 17	434900 17
Steel contact point Type 18/5	434900 18/5
Steel contact point Type 18/2	434900 18/2
Steel contact point Type 30/10	434900 30/10
Connection cable Duplex Type 2	498950 2
Steel contact point Type 2	434900 2
Steel contact point Type 24	434900 24
Steel contact point Type 14/30	434900 14/30

Steel contact point Type 14/40	434900 14/40
Steel contact point Type 18/4	434900 18/4
Steel contact point Type 29/10	434900 29/10
Steel contact point Type 39	434900 39
Steel contact point Type 18/1	434900 18/1
Steel contact point Type 29/20	434900 29/20
Steel contact point Type 12	434900 12
Accessories for calipers Type TAST	417701 TAST
Accessories for calipers Type BUCHSE	417701 BUCHSE