



Digital depth gauge TWIN CAL IP 67, Measuring range: 300 mm



Order data

Order number	418695 300
GTIN	7630041106503
Item class	45A

Description

Version:

Large digital display 11 mm, IP67 protection, "Soft touch" casing, 12,000hours service life, automatic standby after 10min. and automatic shutdown after 2h, TLC-TWIN interface, offset measuring face 4 mm wide.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

General purpose use for depth measurement, holes, offsets, width and spacing measurements.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Interface: Digimatic interface

Interface: USB interface

Interface: TESA Link Connector TLC

IP Index of Protection: IP 67

Calibration: A1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.03 mm

Bridge length: 150 mm

Cross-section measuring beam: 15x4 mm

Technical description

Measuring range	0 - 300 mm
Cross-section measuring beam	15×4 mm
Calibration	A1
Interface	Digimatic interface
Interface	USB interface
Interface	TESA Link Connector TLC
Working time	12000 h
Bridge length	150 mm
Digit height LCD display	11 mm
Reversible reading	0.0005 inch
Reversible reading	0.01 mm
Error limit	0.03 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300

DAkKS calibration Calipers / depth gauges maximum measuring range 300 mm	021010 300
Calibration Calipers / depth gauges maximum measuring range 300 mm	021000 300

Accessories

Data cable TLC, 2 m Type USB	498918 USB
Radio transmitter TLC-TWIN Type SENDER	498916 SENDER
Receiver / USB keyboard interface Type	498965
Software Data-Direct	498925
Button cell / special battery Battery type CR2032	081560 CR2032
Radio receiver TWIN Station Type STATION	498917 STATION
Transmitter Type S121	498966 S121
Stat-Express software	498926
Data cable TLC, 2 m Type D	498918 D
Multi-receiver / USB keyboard interface Type	498975