



Digital depth gauge TWIN CAL IP 67, Measuring range: 500 mm



Order data

Order number	418697 500
GTIN	7630041106572
Item class	45A

Description

Version:

Large digital display 11 mm, IP67 protection, "Soft touch" casing, 12,000hours service life, automatic standby after 10min. and automatic shutdown after 2h, TLC-TWIN interface, offset measuring face 4 mm wide.

With 360° adjustable stop plate for comprehensive measurement tasks.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

General purpose use for depth measurement, holes, offsets, width and spacing measurements.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498918, radio No. 498921 size BT.

Packaging: sturdy box

Interface: USB interface

Interface: Digimatic interface

Interface: TESA Link Connector TLC

IP Index of Protection: IP 67

Calibration: A1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.03 mm

Bridge length: 150 mm

Cross-section measuring beam: 15×4 mm

Technical description

Cross-section measuring beam	15×4 mm
Calibration	A1
Interface	USB interface
Interface	Digimatic interface
Interface	TESA Link Connector TLC
Reversible reading	0.01 mm
Reversible reading	0.0005 inch
Error limit	0.03 mm
Bridge length	150 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

Calibration Calipers / depth gauges maximum measuring range 500 mm	011030 500
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 500 mm	011050 500
Calibration Calipers / depth gauges maximum measuring range 500 mm	021000 500

DAkKS calibration Calipers / depth gauges maximum measuring range 500 mm

021010 500

Accessories

Software Data-Direct

498925

Data cable TLC, 2 m Type D

498918 D

Stat-Express software

498926

Button cell / special battery Battery type CR2032

081560 CR2032

Radio receiver TWIN Station Type STATION

498917 STATION

Receiver / USB keyboard interface Type

498965

Data cable TLC, 2 m Type USB

498918 USB

Transmitter Type S121

498966 S121

Radio transmitter TLC-TWIN Type SENDER

498916 SENDER

Multi-receiver / USB keyboard interface Type

498975