



Digital depth gauge, Measuring range: 300 mm



Order data

Order number	418742 300
GTIN	4045197771209
Item class	41Z

Description

Version:

Measured result is displayed in easy-to-read digits. The measuring faces are precision lapped.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Extension base No. 418744.

Packaging: sturdy box

Calibration: A1

Scale divisions: 0.01 mm

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.04 mm

Bridge length: 100 mm

Cross-section measuring beam: 16x4 mm

Technical description

Scale divisions	0.01 mm
Reversible reading	0.0005 inch
Error limit	0.04 mm
Bridge length	100 mm
Reversible reading	0.01 mm
Calibration	A1

Cross-section measuring beam	16×4 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / Inch
Measured value saving	once-off setting of the zero position
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	021010 300
Calibration Calipers / depth gauges maximum measuring range 300 mm	021000 300

Accessories

Receiver / USB keyboard interface Type	498965
Connecting cable with data switch Type D2	497100 D2
Button cell / special battery Battery type CR2032	081560 CR2032
Multi-receiver / USB keyboard interface Type	498975
Connecting cable Type D1	497080 D1

Connecting cable Type USB2	497080 USB2
Connecting cable with data switch Type USB2	497100 USB2
Screw for depth gauge holder	412230
Transmitter Type S1	498966 S1
Connecting cable with data switch Type D1	497100 D1
Connecting cable Type D2	497080 D2