

**Digital depth gauge, Måleområde: 50 mm****Order data**

Order number	418760 50
GTIN	4045197927682
Item class	42A

Description**Version:**

Digital depth gauge with **absolute scale**, no zeroing required. Very high accuracy due to the glass scale. Electronics switch off automatically after approx. 5 minutes and switch on again as soon as the tool is moved.

Supplied with:

1 battery No. 081560 size CR2032.

Packaging: sturdy box

Calibration: A1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.02 mm

Needle hole probe length: 6 mm

Needle hole probe Ø: 1.5 mm

Bridge length: 50 mm

Technical description

Article no of the battery / rechargeable battery fitted	081560 CR2032
Calibration	A1
Reversible reading	0.01 mm
Reversible reading	0.0005 inch
Needle hole probe length	6 mm

Needle hole probe Ø	1.5 mm
Error limit	0.02 mm
Bridge length	50 mm
Number of batteries contained	1
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measured value saving	once-off setting of the zero position
Measurement technology	digital
all parts	hardened
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940

Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
---	---------------