



## Digital universal depth gauge, Measuring range: 400 mm



### Order data

Order number	418770 400
GTIN	2050001670861
Item class	46P

### Description

#### Version:

Flexible universal depth gauges with exchangeable measuring tips. For measuring cut-outs, grooves, recesses, shoulders etc. Precision lapped measuring faces.

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

Depth gauge, double hook measuring tip No. 418772 size A, 1 battery No. 081560 size CR2032.

#### Optional extras:

Data cable No. 498948.

Measuring tips No. 418772.

Measurement head No. 418774.

Packaging: sturdy box

Interface: RS232 interface

Interface: USB interface

IP Index of Protection: IP 67

Calibration: A2

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.03 mm

Bridge length: 150 mm

Cross-section measuring beam: 12x4 mm

### Technical description

Bridge length	150 mm
---------------	--------

Calibration	A2
Measuring range	0 - 400 mm
Interface	RS232 interface
Interface	USB interface
Cross-section measuring beam	12×4 mm
Reversible reading	0.0005 inch
Reversible reading	0.01 mm
Error limit	0.03 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

## Services

Calibration Vernier hook depth gauge maximum measuring range 500 mm	011200 500
Labelling laser-etched Type	018940
DAkkS calibration Vernier hook depth gauge maximum measuring range 500 mm	011250 500
Calibration Vernier hook depth gauge maximum measuring range 500 mm	021220 500
DAkkS calibration Vernier hook depth gauge maximum measuring range 500 mm	021230 500

## Accessories

Measurement head for depth gauge No. 418770 Bridge length 500 mm	418774 500
Connection cable Duplex Type 2	498950 2
Measuring tip for depth gauge No. 418770 Type A	418772 A
Measurement head for depth gauge No. 418770 Bridge length 600 mm	418774 600
Measuring tip for depth gauge No. 418770 Type C	418772 C
Measuring tip for depth gauge No. 418770 Type B	418772 B
Button cell / special battery Battery type CR2032	081560 CR2032
Measuring tip for depth gauge No. 418770 Type D	418772 D
Measurement head for depth gauge No. 418770 Bridge length 400 mm	418774 400
Connection cable Duplex Type USB2	498950 USB2
Receiver / USB keyboard interface Type	498965
Multi-receiver / USB keyboard interface Type	498975
Transmitter Type S6	498966 S6