



Digital depth gauge, Measuring range: 500 mm



Order data

Order number	418802 500
GTIN	4045197528896
Item class	42A

Description

Version:

Easy-to-read display. Optimum sliding characteristics are ensured by **double Vee guides**. Measurement head of hard-coated aluminium with two tapped holes at 90° (M2.5) to take the measuring tips.

Supplied with:

Contact point No.434900 size2, 3measurement heads (150, 300 and 450 mm), 1battery No.081560 size LR44 and manufacturer's test certificate.

Optional extras:

All spare and special contact points No. 434900 - 4915 with M2.5 thread.

Packaging: sturdy box

Calibration: A1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.05 mm

Cross-section measuring beam: 23.5 × 9 mm

Technical description

Cross-section measuring beam	23.5 × 9 mm
Calibration	A1
Measuring range	0 - 500 mm
Reversible reading	0.0005 inch
Reversible reading	0.01 mm

Error limit	0.05 mm
Article no of the battery / rechargeable battery fitted	081560 LR44
Number of batteries contained	1
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measurement technology	digital
Test certificate	Manufacturer's test certificate
Packaging	sturdy box
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

Calibration Calipers / depth gauges maximum measuring range 500 mm	011030 500
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 500 mm	011050 500

Accessories

Steel contact point Type 2	434900 2
Ruby contact point Type 2	434915 2
Carbide contact point Type 2	434910 2
Button cell / special battery Battery type LR44	081560 LR44
Steel contact point Type 13	434900 13
Steel contact point Type 15	434900 15
Steel contact point Type 11/25	434900 11/25
Carbide contact point Type 18/1	434910 18/1
Steel contact point Type 18/1	434900 18/1
Carbide contact point Type 18/2	434910 18/2
Steel contact point Type 24	434900 24

Steel contact point Type 14/40	434900 14/40
Carbide contact point Type 18/3	434910 18/3
Carbide contact point Type 16	434910 16
Steel contact point Type 17	434900 17
Steel contact point Type 14	434900 14
Steel contact point Type 14/15	434900 14/15
Steel contact point Type 11/15	434900 11/15
Steel contact point Type 18/2	434900 18/2
Carbide contact point Type 11	434910 11
Carbide contact point Type 18/4	434910 18/4
Steel contact point Type 18/5	434900 18/5
Steel contact point Type 18/4	434900 18/4
Steel contact point Type 11/30	434900 11/30
Steel contact point Type 29/20	434900 29/20
Steel contact point Type 12	434900 12
Steel contact point Type 18/3	434900 18/3
Steel contact point Type 11/35	434900 11/35
Steel contact point Type 30/10	434900 30/10
Steel contact point Type 14/30	434900 14/30
Steel contact point Type 20	434900 20
Steel contact point Type 28	434900 28
Steel contact point Type 11	434900 11
Steel contact point Type 39	434900 39
Carbide contact point Type 18/6	434910 18/6
Carbide contact point Type 14	434910 14
Steel contact point Type 10	434900 10
Steel contact point Type 29/10	434900 29/10
Steel contact point Type 18/6	434900 18/6
Steel contact point Type 16	434900 16

Carbide contact point Type 10	434910 10
Steel contact point Type 11/20	434900 11/20
Carbide contact point Type 18/5	434910 18/5
Carbide contact point Type 17	434910 17
Steel contact point Type 14/20	434900 14/20