

**Garant**
**External micrometer, Measuring range: 25-50 mm**

**Order data**

Order number	420402 25-50
GTIN	4045197367334
Item class	41B

**Description**
**Version:**
**Precision lapped, carbide-tipped measuring faces.**

Hardened and ground measuring spindle. Locking by clamping lever.

With ratchet and hand temperature protection. Barrel non-reflecting chrome-plated.

With clearly engraved, black divisions and numerals.

**With combined sensitive ratchet for one-hand operation and operation within the bracket.**

**Supplied with:**

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Spindle Ø: 6.5 mm

Barrel Ø: 19 mm

**Technical description**

Measuring range	25 - 50 mm
Spindle Ø	6.5 mm
Scale divisions	0.01 mm

Number of micrometer standards	1
Micrometer barrel graduations	1/50 mm
Barrel Ø	19 mm
Calibration	B1
Calibration	B2
Standard	DIN 863
Ratchet	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

## Services

Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
100	022090 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100

## Accessories

Micrometer setting standard overall length 25 mm	421100 25
--	-----------