

 Mahr**External micrometer, Measuring range: 100-125 mm****Order data**

Order number	420410 100-125
GTIN	4059192003685
Item class	43A

**Description****Version:****Precision lapped, carbide-tipped measuring faces.**

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

**Supplied with:**

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 6 µm

Spindle Ø: 6.5 mm

Barrel Ø: 17.5 mm

**Technical description**

Scale divisions	0.01 mm
Barrel Ø	17.5 mm

Micrometer barrel graduations	1/50 mm
Spindle Ø	6.5 mm
Measuring range	100 - 125 mm
Calibration	B2
Calibration	B2
Calibration	B1
Error limit	6 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

## Services

Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 200 mm	022000 200
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
100	022090 100

## Accessories

Micrometer setting standard overall length 100 mm	421100 100
---	------------