



External micrometer, Measuring range: 0-25 mm



Order data

Order number	420430 0-25
GTIN	4062406237509
Item class	42B

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle. Locking by clamping lever.

With ratchet and hand temperature protection. Barrel non-reflecting chrome-plated.

With clearly engraved, black divisions and numerals.

With combined sensitive ratchet for one-hand operation and operation within the bracket.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Spindle Ø: 6.5 mm

Barrel Ø: 20.5 mm

Technical description

Measuring range	0 - 25 mm
Calibration	B1
Scale divisions	0.01 mm
Barrel Ø	20.5 mm
Spindle Ø	6.5 mm

Micrometer barrel graduations	1/50 mm
Standard	DIN 863
Ratchet	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	micrometer

Services

DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 25 mm	012050 25