



External micrometer, Measuring range: 50-75 mm



Order data

Order number	420430 50-75
GTIN	4062406237721
Item class	42B

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle. Locking by clamping lever.

With ratchet and hand temperature protection. Barrel non-reflecting chrome-plated.

With clearly engraved, black divisions and numerals.

With combined sensitive ratchet for one-hand operation and operation within the bracket.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Spindle Ø: 6.5 mm

Barrel Ø: 20.5 mm

Technical description

Micrometer barrel graduations	1/50 mm
Calibration	B2
Calibration	B1
Barrel Ø	20.5 mm

Scale divisions	0.01 mm
Spindle Ø	6.5 mm
Measuring range	50 - 75 mm
Standard	DIN 863
Ratchet	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	micrometer

Services

Calibration External tube micrometer maximum measuring range 100 mm	012050 100
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Labelling laser-etched Type	018940

Accessories

Micrometer setting standard overall length 50 mm	421100 50
--	-----------