

HOLEX®
External micrometer, Measuring range: 75-100 mm

Order data

Order number	420430 75-100
GTIN	4062406237738
Item class	42B

Description
Version:
Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle. Locking by clamping lever.

With ratchet and hand temperature protection. Barrel non-reflecting chrome-plated.

With clearly engraved, black divisions and numerals.

With combined sensitive ratchet for one-hand operation and operation within the bracket.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Spindle Ø: 6.5 mm

Barrel Ø: 20.5 mm

Technical description

Measuring range	75 - 100 mm
Calibration	B1
Calibration	B2
Micrometer barrel graduations	1/50 mm

Scale divisions	0.01 mm
Barrel Ø	20.5 mm
Spindle Ø	6.5 mm
Standard	DIN 863
Ratchet	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	micrometer

Services

Labelling laser-etched Type	018940
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100

Accessories

Micrometer setting standard overall length 75 mm	421100 75
--	-----------