



## External micrometer, Measuring range: 50-75 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 420450 50-75  |
| GTIN         | 7630041104103 |
| Item class   | 45A           |

### Description

#### Version:

#### Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 2  $\mu$ m

Spindle  $\varnothing$ : 6.5 mm

Barrel  $\varnothing$ : 18.5 mm

### Technical description

|                               |            |
|-------------------------------|------------|
| Barrel $\varnothing$          | 18.5 mm    |
| Micrometer barrel graduations | 1/50 mm    |
| Scale divisions               | 0.01 mm    |
| Measuring range               | 50 - 75 mm |

|                        |                          |
|------------------------|--------------------------|
| Spindle Ø              | 6.5 mm                   |
| Calibration            | B2                       |
| Calibration            | B2                       |
| Calibration            | B1                       |
| Error limit            | 2 µm                     |
| Standard               | DIN 863                  |
| Measurement technology | analogue                 |
| Packaging              | sturdy box               |
| Type of product        | External tube micrometer |

## Services

|   |            |
|---|------------|
| Calibration External tube micrometer maximum measuring range 100 mm                 | 012050 100 |
| Calibration Micrometer standard for external micrometer maximum nominal size 100 mm | 012110 100 |
| Labelling laser-etched Type   | 018940     |
| DAkkS calibration External micrometer maximum measuring range 100 mm                | 012060 100 |
| Calibration External tube micrometer maximum measuring range 100 mm                 | 022000 100 |
| Calibration Micrometer standard for external micrometer maximum nominal size 100 mm | 022080 100 |
| 100   | 022090 100 |
| DAkkS calibration External micrometer maximum measuring range 100 mm                | 022010 100 |

## Accessories

|  |           |
|--|-----------|
| Micrometer setting standard overall length 50 mm | 421100 50 |
|--|-----------|