



External micrometer, Measuring range: 75-100 mm



Order data

Order number	420450 75-100
GTIN	7630041104110
Item class	45A

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 3 μ m

Spindle \varnothing : 6.5 mm

Barrel \varnothing : 18.5 mm

Technical description

Spindle \varnothing	6.5 mm
Barrel \varnothing	18.5 mm
Micrometer barrel graduations	1/50 mm
Measuring range	75 - 100 mm

Scale divisions	0.01 mm
Calibration	B2
Calibration	B2
Calibration	B1
Error limit	3 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
100	022090 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100

Accessories

Micrometer setting standard overall length 75 mm	421100 75
--	-----------