

Mitutoyo
External micrometer, Measuring range: 0-25 mm

Order data

Order number	420500 0-25
GTIN	4946368385624
Item class	44A

Description
Version:
Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

From size 100-125, enamelled cast frame.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 2 μ m

Spindle \varnothing : 6.35 mm

Barrel \varnothing : 18 mm

Technical description

Measuring range	0 - 25 mm
Micrometer barrel graduations	1/50 mm
Barrel \varnothing	18 mm

Spindle pitch	1/50 mm
Spindle Ø	6.35 mm
Type of measurement face	carbide tipped
Scale divisions	0.01 mm
Calibration	B1
Error limit	2 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100