

Mitutoyo
External micrometer, Measuring range: 125-150 mm

Order data

Order number	420500 125-150
GTIN	4946368214986
Item class	44A

Description
Version:
Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

From size 100-125, enamelled cast frame.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 3 μ m

Spindle \varnothing : 6.35 mm

Barrel \varnothing : 18 mm

Technical description

Scale divisions	0.01 mm
Micrometer barrel graduations	1/50 mm

Type of measurement face	Carbide tipped
Spindle pitch	1/50 mm
Spindle Ø	6.35 mm
Measuring range	125 - 150 mm
Barrel Ø	18 mm
Calibration	B2
Calibration	B2
Calibration	B1
Error limit	3 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Labelling laser-etched Type	018940
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	012110 300
Calibration External tube micrometer maximum measuring range 200 mm	012050 200
900	022090 900
Calibration External tube micrometer maximum measuring range 200 mm	022000 200
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	022080 300