

Mitutoyo
External micrometer, Measuring range: 200-225 mm

Order data

Order number	420500 200-225
GTIN	4946368215013
Item class	44A

Description
Version:
Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

From size 100-125, enamelled cast frame.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 4 μ m

Spindle \varnothing : 6.35 mm

Barrel \varnothing : 18 mm

Technical description

Barrel \varnothing	18 mm
Micrometer barrel graduations	1/50 mm
Spindle pitch	1/50 mm

Measuring range	200 - 225 mm
Scale divisions	0.01 mm
Spindle Ø	6.35 mm
Type of measurement face	Carbide tipped
Calibration	B2
Calibration	B1
Error limit	4 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	micrometer

Services

Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	012110 300
Calibration External tube micrometer maximum measuring range 300 mm	012050 300
Labelling laser-etched Type	018940