

**Mitutoyo**
**External micrometer, Measuring range: 225-250 mm**

**Order data**

Order number	420500 225-250
GTIN	4946368215020
Item class	44A

**Description**
**Version:**
**Precision lapped, carbide-tipped measuring faces.**

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

From size 100-125, enamelled cast frame.

**Supplied with:**

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 5  $\mu$ m

Spindle  $\varnothing$ : 6.35 mm

Barrel  $\varnothing$ : 18 mm

**Technical description**

Scale divisions	0.01 mm
Barrel $\varnothing$	18 mm

Spindle Ø	6.35 mm
Measuring range	225 - 250 mm
Micrometer barrel graduations	1/50 mm
Type of measurement face	Carbide tipped
Spindle pitch	1/50 mm
Calibration	B2
Calibration	B2
Calibration	B1
Error limit	5 µm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

## Services

Calibration External tube micrometer maximum measuring range 300 mm	012050 300
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	012110 300
Labelling laser-etched Type	018940
900	022090 900
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	022080 300
Calibration External tube micrometer maximum measuring range 300 mm	022000 300