



## External micrometer, Measuring range: 0-25 mm



### Order data

Order number	420542 0-25
GTIN	4250099600209
Item class	46P

### Description

#### Version:

**Precision lapped, carbide-tipped measuring faces.** Hardened and ground measuring spindle. Higher accuracy than DIN 863. Locking by clamping screw. With sensitive ratchet and hand temperature protection. Clearly engraved black divisions and numerals.

#### Application:

Particularly suitable for inspection work due to the direct 5 µm reading.

Packaging: sturdy box

Standard: Manufacturer's standard

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.005 mm

Error limit: 1.5 µm

Spindle Ø: 8 mm

Barrel Ø: 25 mm

### Technical description

Scale divisions	0.005 mm
Calibration	B1
Micrometer barrel graduations	1/50 mm
Error limit	1.5 µm
Barrel Ø	25 mm

Measuring range	0 - 25 mm
Type of spindle	hardened and ground
Spindle Ø	8 mm
Standard	Manufacturer's standard
Ratchet	yes
Hand temperature protection	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

### Services

DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25