

**Mitutoyo**
**External micrometer Inch graduations, Measuring range: 1-2 inches**

**Order data**

Order number	420600 1-2
GTIN	4946368003566
Item class	44A

**Description**
**Version:**

Barrel non-reflecting chrome plated.

**Precision lapped, carbide-tipped measuring faces.** Hardened and ground measuring spindle. Locking by locking lever. With ratchet. Precision engraved black divisions and numerals.

**Supplied with:**

From size 1-2 including 1 setting standard.

Packaging: sturdy box

Standard: Manufacturer's standard

Calibration: B1

Calibration: B2

Scale divisions: 0.0001 inch

Spindle Ø: 6.35 mm

Barrel Ø: 18 mm

**Technical description**

Barrel Ø	18 mm
Type of measurement face	carbide tipped
Calibration	B1
Calibration	B2
Spindle Ø	6.35 mm
Measuring range	1 - 2 mm

Scale divisions	0.0001 inch
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

### Services

Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
100	022090 100

### Accessories

Micrometer setting standard overall length 1 inches	421150 1
-----------------------------------------------------	----------