



External micrometer 1/100 graduations, Measuring range: 50-75 mm



Order data

Order number	420750 50-75
GTIN	4045197203878
Item class	42B

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle; with locking lever
With ratchet and hand temperature protection.

Supplied with:

From size 25 – 50 supplied with 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/100 mm

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Spindle Ø: 8 mm

Barrel Ø: 30 mm

Technical description

Barrel Ø	30 mm
Scale divisions	0.01 mm
Spindle Ø	8 mm
Measuring range	50 - 75 mm
Micrometer barrel graduations	1/100 mm

Calibration	B2
Calibration	B1
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Labelling laser-etched Type	018940
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
100	022090 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100

Accessories

Micrometer setting standard overall length 50 mm	421100 50
--	-----------