

Hartig

Precision external micrometer with 50 mm spindle travel, Measuring range: 0-50 mm



Order data

Order number	420900 0-50
GTIN	4250099609189
Item class	46P

Description

Version:

Stable spheroidal cast frame, hammer finish with hand temperature protection, friction clutch, and locking device. Precision lapped, carbide-tipped measuring faces. Accuracy better than DIN 863.

Advantage:

50 mm spindle travel, ideal for larger measurement ranges. Direct reading of the 1/100 mm on the large scale barrel.

Supplied with:

Without setting standard.

Packaging: sturdy box

Standard: Manufacturer's standard

Micrometer barrel graduations: 1/100 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 3 μ m

Spindle \varnothing : 8 mm

Barrel \varnothing : 24 mm

Technical description

Spindle \varnothing	8 mm
Micrometer barrel graduations	1/100 mm
Measuring range	0 - 50 mm

Barrel Ø	24 mm
Scale divisions	0.01 mm
Calibration	B1
Error limit	3 µm
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100